

Handwritten notes: "Handwritten", "C", "8/9/04", and "K. P. Hall".

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-5. (cancelled)

6. (currently amended) ~~The device of claim 5~~ An input device comprising:

a housing;

electronic circuitry for detecting user inputs and transmitting signals

corresponding to said inputs to an electronic device;

a sleep-mode circuit, coupled to said electronic circuitry, for activating a reduced power operation of said electronic circuitry;

a capacitive hand detection circuit for detecting the proximity of a user's hand to said housing and producing a hand detect signal; and

said sleep mode circuit being responsive to said hand detect signal to awaken said electronic circuitry from said reduced power operation;

wherein said hand detection circuit is mounted inside a top of said housing, such that a portion of said housing insulates said user's hand from said capacitive hand detection circuit;

wherein said capacitive detection circuit comprises

first and second electrodes on said housing for capacitive connection with a user's hand;

a first circuit, coupled to said first electrode, for determining an amount of time for charging of a capacitance connected to said first circuit; and

a second circuit, coupled to said second electrode, for determining an amount of time for discharging of a capacitance connected to said second circuit;

such that an internal virtual ground is produced between said first and second electrodes; and

BEST AVAILABLE COPY

wherein said first circuit comprises:
a comparator;
a controller coupled to an output of said comparator;
a voltage divider feedback circuit coupled between an output and a reference voltage input of said comparator;
a detection capacitor coupled between said first electrode and a signal input of said comparator; and
a switching circuit selectively coupling said signal input of said comparator to high and low voltage supplies.

7-26. (canceled)

²
~~27~~ (currently amended) An input device comprising:

a housing;
electronic circuitry for detecting user inputs and transmitting signals corresponding to said inputs to an electronic device; and
an optical hand detection circuit for optically detecting the proximity of a user's hand to said housing and producing a hand detect signal;
a controller for turning on and off said a light emitter, and providing said hand ~~detect~~ detection signal only after a predetermined number of on cycles provides a reflection to said detector above a threshold, wherein said controller further:
filters ambient light frequencies different from a frequency of said light emitter;
cycles said light emitter on and off at a first rate before a hand detection, and at a second rate after a hand detection; and
requires detection of a hand for a predetermined number of cycles before issuing said hand detect signal.

³
~~28~~ (original) The input device of claim ²~~27~~ wherein said controller removes said hand detect signal in the absence of a control input to said input device for a predetermined amount of time after a detection of a hand.

Appl. No. 09/964,975

Amdt. dated June 25, 2004

Reply to Final Office Action of February 26, 2004

PATENT

~~29~~⁴. (previously presented) The input device of claim ~~27~~³ wherein said input device is a mouse.

~~30~~⁵. (previously presented) The input device of claim ~~27~~² further comprising:
a sleep-mode circuit, coupled to said electronic circuitry, for activating a reduced power operation of said electronic circuitry, said sleep mode circuit being responsive to said hand detect signal to awaken said electronic circuitry from said reduced power operation.

31. (canceled)

BEST AVAILABLE COPY